

Admonter elastic adhesive



Suitable for using in private and public areas

Your advantage:

- suitable for all Admonter products
- no swelling and fading thanks to ingredients free of solvent and water
- perfect for laying Admonter FLOORs on based temperature-underfloor heating systems
- reduced formation of joints during heating period because of permanently elastic behaviour
- sound isolation increase
- reduced room sound
- free of solvent and isocyanat/"EC1 plus"-certificated, GEV EMICODE
- general building inspectorate approval, emission-proved general building
- no use of high effort and high costs with pre-working on difficult undergrounds. Direct gluing on almost all ground-levels, solid and free of fat and dust undergrounds without additional ground coat possible.
- high laying comfort - guter Rippenstand
- long laying time
- gluing rests can be easily removed from parquet surface
- ready for use, that means no need of stiring or measuring
- reach: approx. 1kg/m² (16kg / package)



For detailed processing instructions, see label on the container



Admonter
Holzindustrie AG

8911 Admont / Austria, Sägestraße 539

phone: +43(0)3613/3350-0, fax: +43(0)3613/3350-119, e-mail: info@admonter.at

FN237499p (LG Leoben) Gerichtsstand Liezen, UID-Nr.: ATU57198366

Bankverbindung: Raiffeisenbank Admont, IBAN: AT88 3800 1000 0002 7276, BIC: RZSTAT2G001

