



Admonter on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems.

We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit www.admonter.eu/en/downloads/.

PLEASE NOTE: natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! Repair and supplementary oils you can find in our Admonter price list. Further information about our products can be found at admonter.at

Grading	Thickness (mm)	Construction	Width (mm)	Format	Length (mm)	Texture	Finish	Profile
noblesse	10,5	2-layer	158	classic	2000	brushed	ec	lock-it
			180	classic	2000	brushed	ec	lock-it
	15	3-layer	158	classic	2000 / 2400	brushed	ec	Tongue & groove
			192	classic	2000 / 2400	brushed	ec	Tongue & groove
basic	15	3-layer	158	classic	2000 / 2400	brushed	ec	Tongue & groove
			192	classic	2000 / 2400	brushed	ec	Tongue & groove
			240	classic	2000 / 2400	brushed	ec	Tongue & groove
naturelle	15	3-layer	280	long	2800	brushed	ec	Tongue & groove
rustic	10,5	2-layer	158	classic	2000	brushed	ec	lock-it
			180	classic	2000	brushed	ec	lock-it
	15	3-layer	158	classic	2000 / 2400	brushed	ec	Tongue & groove
					2000	antico	pc	Tongue & groove
			192	classic	2000 / 2400	cross / alpin	ec	Tongue & groove
					2000	brushed	ec	Tongue & groove
			240	classic	2000	antico	pc	Tongue & groove
					2000 / 2400	cross / alpin	ec	Tongue & groove
			240	classic	2000 / 2400	cross / alpin	ec	lock-it
					2000 / 2400	brushed	ec	Tongue & groove
natur	15	3-layer	192/240 280/325	xxlong	3500-5000	brushed	ec	Tongue & groove

Backing: Solid wood / ec: natural oiled easy care / pc: natural oiled pro care / ml: matt lacquered

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/de/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	D-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Oak	10,5	5,7	7+/-2	0,15	0,067	41	C _s -s1
Oak LH-RS	15	8,6	7+/-2	0,15	0,100	41	C _s -s1
Oak NH-RS	15	7,8	7+/-2	0,14	0,107	41	C _s -s1

LH-RS: Hardwood-backing / NH-RS: Softwood-backing



Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples. Errors and changes possible.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at
FN237499p Landesgericht Leoben, Gerichtsstand Liezen | UID-Nr.: ATU57198366

Raiffeisenbank Admont, IBAN: AT88 3800 1000 0002 7276 | BIC: RZSTAT213001 | admonter.com




Room concepts
made of **natural wood** for floors,
walls & ceilings

Wooden floors
Floors



project by Beschneider + Berschneider

Feature wooden floors	Benefit
Choice of countless wood species, in particular reclaimed wood	Wide range of options for customized products, precisely tailored to customer benefits / requirements -> for every customer or area of application.
Different structure possibilities and colour shades	
Individual colours (Easy-Color)	The right finish for every customer or area of application / living situation Finish Video liquid test
Different finishings (natural oiled easy-care / natural oiled pro care / matt lacquered)	
Different construction variants, thicknesses and profiles / installation systems	The right product for every application / purpose
Different formats (SMALL, CLASSIC, LONG, XXLlong)	The right product for every room size and situation
Different widths that can be laid together	Great appearance of the floor in large rooms
Admonter solid wood construction for 3-layer floors (top layer, perpendicular middle layer, backside as a counter layer with solid wood construction) For wood Typee oak 240mm width = hardwood reverse side	Rigid against torsion -> the floor lies flatter and the position of joints is reduced, even with wide plank flooring



Admonter flooring is a 100 % natural product. A picture never replaces the reality. For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples. Errors and changes possible.

Admonter Holzindustrie AG | Sägestraße 539 | 8911 Admont, Austria | info@admonter.at
FN237499p Landesgericht Leoben, Gerichtsstand Liezen | UID-Nr.: ATU57198366

Raiffeisenbank Admont, IBAN: AT88 3800 1000 0002 7276 | BIC: RZSTAT213001 | admonter.com