

**Accompanying information to CE-marking according to EN 14342**

Admonter FLOORs to be used as floor covering for interior use	Reaction to fire classification according to EN14342 chart 1 after fire inspection according to EN 13501-1								Thermal conductivity W/mK				Emission of formaldehyde	Biological durability	Slipperiness**	
	Class	Thickness (mm)				Density kg/m <sup>3</sup>	Finish		Installation	Thickness (mm)						
		10	13	15	21		B	W		1	2	10				13
Type of Wood																
<b>Hardwood</b>																
Oak (incl. lightly smoked)	C <sub>fl</sub> -s1	X						X		X			0,15			
	C <sub>fl</sub> -s1			X				X	X					0,14		
	C <sub>fl</sub> -s1		X					X	X				0,14			
	D <sub>fl</sub> -s1			X			≥ 500	X		X				0,14		
Oak thermo dark	C <sub>fl</sub> -s1	X						X		X			0,14			
	C <sub>fl</sub> -s1		X					X	X				0,14			
	C <sub>fl</sub> -s1			X				X		X			0,14			
Oak thermo medium	C <sub>fl</sub> -s1	X						X		X			0,14			
	C <sub>fl</sub> -s1		X					X		X			0,14			
	C <sub>fl</sub> -s1			X				X		X			0,14			
Ash	C <sub>fl</sub> -s1			X				X	X				0,14			
	D <sub>fl</sub> -s1			X			≥ 500	X		X						
American Cherry	C <sub>fl</sub> -s1			X				X	X				0,15			
	D <sub>fl</sub> -s1			X			≥ 500	X		X						
American Walnut	C <sub>fl</sub> -s1			X				X	X				0,15			
	D <sub>fl</sub> -s1			X			≥ 500	X		X						
	C <sub>fl</sub> -s1		X					X	X				0,15			
	D <sub>fl</sub> -s1		X				≥ 500	X		X						
	C <sub>fl</sub> -s1	X						X		X			0,15			
<b>Softwood</b>																
Larch thermo	C <sub>fl</sub> -s1			X				X	X				0,14			
Lärche (incl. steamed)	C <sub>fl</sub> -s1			X				X	X				0,15			
	D <sub>fl</sub> -s1			X			≥ 500	X		X			0,15			
Spruce	C <sub>fl</sub> -s1			X				X		X			0,15			
Stone-Pine (14mm)	F <sub>fl</sub>							X	X	X			0,12			
Pine	F <sub>fl</sub>			X				X	X	X			0,14			
<b>2-strip Admonter TEC (Top layer 2,5mm)</b>																
Oak	C <sub>fl</sub> -s1	X						X		X			0,15			
<b>2-strip Admonter TEC (Top layer 2,5mm)</b>																
Oak	B <sub>fl</sub> -s1	X						X		X			0,15			
<b>Selection Textures</b>																
American Walnut antico	C <sub>fl</sub> -s1			X				X	X				0,15			

## Accompanying information to CE-marking according to EN 14342

Selection Reclaimed Wood																
Reclaimed Wood multi-strip	C <sub>0</sub> -s1			X				X		X			0,15	E1	class 1	NPD
Reclaimed Wood extreme multi-strip	F <sub>0</sub>						X	X	X				0,15			
Reclaimed Wood Oak	C <sub>0</sub> -s1			X				X	X				0,15			
Selection Twin																
Twin Oak (incl. lightly smoked)	C <sub>0</sub> -s1	X						X		X			0,15	E1	class 1	39
	C <sub>0</sub> -s1			X				X		X			0,15			
Twin Oak thermo medium	C <sub>0</sub> -s1			X				X		X			0,14			
Twin American Walnut	C <sub>0</sub> -s1	X						X		X			0,14			
	C <sub>0</sub> -s1			X				X		X			0,15			NPD
Selection Chevron																
Oak	C <sub>0</sub> -s1			X				X	X				0,15	E1	class 1	39
	C <sub>0</sub> -s1	X						X		X			0,15			
Oak thermo medium	C <sub>0</sub> -s1			X				X	X				0,14			
Larch	C <sub>0</sub> -s1	X						X		X			0,15			
American Walnut	C <sub>0</sub> -s1			X				X	X				0,15			NPD
Selection Long + xxlong																
Oak (incl. lightly smoked)	C <sub>0</sub> -s1			X				X	X				0,15	E1	class 1	39
Larch	C <sub>0</sub> -s1			X				X	X				0,15			
Spruce	C <sub>0</sub> -s1			X				X	X				0,15			
Ondo (Top layer 2,5mm)																
Oak (incl. lightly smoked)	C <sub>0</sub> -s1		X					X	X				0,14	E1	class 1	39,0
Oak Jesper (thermo-treated)	C <sub>0</sub> -s1		X					X	X				0,14			

### Notes:

Finish B: on-site surface treatment according to EN 14342 chart 1 (For surface-treatment the following is allowed to be used:

Acryl, Polyurethan and soap, (50 to 100) g/m<sup>2</sup>, or oil, (20 to 60) g/m<sup>2</sup>.

Finish W: factory made surface treatment

Installation 1: all types of installation (on floor joists, floating, full surface stick down installation) possible; (installation according to EN 14342 chart 1);

hickness < 15 mm only full surface stick down installation

Installation 2: subfloor: cement screed or subfloor corresponding to the euro-class A1fl or A2fl and a minimal density of 1350 kg/m<sup>3</sup>

Type of installation: full surface stick down installation with parquet adhesive usual in the trade

\*\*\*) values for all oiled surfaces , value in ( ) oil-surfaces exclusively brushed

NPD – no property determined

Admont, 15. June 2020