

# CHEVRON OAK GREY

3-Layer top layer approx. 3,6 mm

Initial oil treatment required!



**FLOORs**



Illustration noblesse



**Please note 10 mm/supporting material HDF:**  
Not suitable for use in the bathroom according to data sheet "Admonter in bathroom".



### Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive. However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small, they have to be fully glued down). We recommend hot-water underfloor heating systems set at low temperature. Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

### Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes flush-mount skirting and solutions for staircases.

### Regular care and maintenance

Please see the Admonter maintenance & installation instructions or visit [www.admonter.com/en/downloads/](http://www.admonter.com/en/downloads/).

**PLEASE NOTE:** natural oiled easy care - NO INITIAL OIL TREATMENT IS REQUIRED! Repair and supplementary oils you can find in our Admonter price list. Further information about our products can be found at [admonter.com](http://admonter.com)

Grading	Thickness (mm)	Construction	Width (mm)	Length (mm)	Texture	Texture	Profile
noblesse	45°	3-Layer	120	500	brushed	ec	Tongue & groove
	60°	3-Layer	120	525	brushed	ec	Tongue & groove
basic	45°	3-Layer	120	500	brushed	ec	Tongue & groove
	60°	3-Layer	120	525	brushed	ec	Tongue & groove

Backing: 3-Layer = Solid wood / ec: natural oiled easy care

### Please note:

Small formats have to be glued-down with Admonter elastic adhesive over the entire surface. Only left or right elements per package unit!

To achieve an optimal protection of the bevel an INITIAL CARE is absolutely necessary (see pictures).

The right Admonter maintenance oil for initial care is automatically included in the delivery in your own invoice item.

Bevel without initial care



Bevel with initial care



Repair and supplementary oils are available on request.

### Natural color changes:

All Admonter floors are a natural product and will over time change colour. Depending on the amount of exposure your floor has to sunlight, lighter timber will turn darker and darker timber will become lighter. This change is most pronounced in the first 3-6 months.

### Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.com/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m <sup>2</sup> ]	Moisture content [%]	Lambda [W/m K]	d-Value R [m <sup>2</sup> K/W]	Hardness [N/mm <sup>2</sup> ]	Fire classification
Oak	15	8,6	7+/-2	0,15	0,100	41	C <sub>1</sub> -s1

