


TWIN OAK LAPIS *lightly smoked*

Top layer approx. 3,6 mm

Maintenance oil white



symbolic photo

Admonter FLOORs on underfloor heating systems

Admonter FLOORs are ideally suited for underfloor heating systems. We recommend hot-water underfloor heating systems set at low temperature.



Please find detailed information in the information sheet Admonter FLOORs on underfloor heating systems!

Admonter accessories

The wide range of accessories matches the Admonter FLOORs and includes matching boarders, flush-mount skirting and solutions for staircases.

Regular care and maintenance

Please see the Admonter maintenance & installation instructions for small format floorboards.

Further information

<http://www.admonter.eu/en/downloads/>

Grading	Thickness (mm)	Construction	Width (mm)	Length (mm)	Texture	Finish	Profile
noblesse	15	3-Layer	120	small	sanded / brushed	ec	Tongue & groove
basic	15	3-Layer	120	small	sanded / brushed	ec	Tongue & groove

Backing: Solid Wood / ec: natural oiled easy care / ml: matt lacquer

Please note:

Repair and supplementary oils can be found in the Admonter price list.

Technical information

More information (for example concerning fire classification) in the accompanying information to CE-marking at <http://www.admonter.eu/en/downloads/>

Type of wood	Thickness (mm)	Weight [kg/m ²]	Moisture content [%]	Lambda [W/m K]	d-Value R [m ² K/W]	Hardness [N/mm ²]	Fire classification
Oak	10	5,7	7+/-2	0,15	0,067	41	C _s -s1
Oak	15	8,6	7+/-2	0,15	0,100	41	C _s -s1

